

# ARIN THERMOSTATIC SHOWER SYSTEM WITH HAND SHOWER & 6 BODY SPRAYS

SKU: 927745

Code: SH405702, SH405374, SH414749



## FEATURES

Material: Brass

Shower Head Swivel: No

Hand Shower Spray: Full

Hand Shower Flow Rate: 1.8 gpm (6.8 L/min) @ 80 psi

Connection Type: 1/2" IPS

Diverter Outlets: 3

Cartridge Type: Thermostatic

ASME A112.18.1/CSA B125.1



## ADDITIONAL FEATURES

- Shower system includes wall mount rainfall/waterfall shower head, wall mount hand shower, hand shower water connection, 6 body sprays and a thermostatic 3-way in-wall diverter.
- Shower head has a standard spray and a waterfall feature.
  - Standard spray flow rate: 1.8 gpm (6.8L/min) max @ 80 psi
  - Waterfall flow rate: 2.5 gpm (9.5L/min) max @ 80 psi
- Body spray flow rate: 1.8 gpm (6.8L/min) max @ 80 psi
- Thermostatic technology keeps shower temperature  $\pm 1$  degree Celsius.
- Hand shower water connection features a 1/2" IPS connection.
- 3-way diverter features 1/2" IPS inlets, and controls water flow between 3 shower outlets.
- Diverter includes the valve and metal lever handles.

REVISED 6/5/2024