HIBISCUS THERMOSTATIC SHOWER SYSTEM WITH DUAL SHOWERHEADS AND HAND SHOWER

SKU: 953895

Code: SHHB9009,SH6006,SHRSA120S,SHSH2080G,SHHS4080G,SHH1010,SHWES2050,SHHB9005,SH6103,SHHB9007,SH6040, SHHB9009Z,SH6006,SHRSA120SZ,SHSH2080GZ,SHHS4080GZ,SHH1010Z,SHWES2050,SHHB9005Z,SH6103,SHHB9007Z,SH6040



ASME A112.18.1/CSA B125.1

ASSE 1016 Type T
ICC/ANSI A117.1
CEC Listed

Massachusetts Accepted
LISTED ID: SHHB9009*, SH6006, SHRSA120S*,
SHSH2080G*, SHHS4080G*, SHH1010*,
SHWES2050xy, SHHB9005*, SH6103, SHHB9007*,
SH6040









FEATURES

Mounting Hardware Included: Yes

Assembly Required: No Handle Type: Lever NPT Connection: 1/2"

Shower Head Installation Type: Wall-Mount

Number of Shower Heads: 2

Shower Head Material: 304-Grade Stainless Steel

Shower Head Spray: Rainfall Shower Head Length: 11-3/4" Shower Head Width: 11-3/4" Shower Arm Included: Yes Shower Arm Extension: 12" Shower Arm Height: 2-3/8" Shower Head IPS: 1/2" Shower Head Swivel: Yes Valve Trim Width: 6-11/16" Valve Trim Height: 6-11/16" Hand Shower Hose Length: 60" Hand Shower Material: Brass

Hand Shower Flow Rate: 1.8 gpm (6.8 L/min) @ 80 psi

Diverter Included: Yes

Shower Head Flow Rate: 1.8 gpm (6.8 L/min) @ 80 psi

HIBISCUS THERMOSTATIC SHOWER SYSTEM WITH DUAL SHOWERHEADS AND HAND SHOWER

SKU: 953895

Code: SHHB9009,SH6006,SHRSA120S,SHSH2080G,SHHS4080G,SHH1010,SHWES2050,SHHB9005,SH6103,SHHB9007,SH6040,SHHB9009Z,SH6006,SHRSA120SZ,SHSH2080GZ,SHHS4080GZ,SHH1010Z,SHWES2050,SHHB9005Z,SH6103,SHHB9007Z,SH6040





ADDITIONAL FEATURES

- Thermostatic technology keeps shower temperature within 1 degree Celsius.
- Temperature outlet factory calibrated to 104 degrees Fahrenheit and can be easily adjusted up or down to user's comfort level.
- Six total settings allow for shared water flow between outlets, giving you the ability to use two functions at once.
- Metal handles.
- Dual single function shower heads (full spray) with easy-clean silicone nozzles.
- Single function hand shower.
- 60" 72" stretchable metal shower hose.
- Adjustable angle for hand shower mount.
- Must be installed in accordance with provided installation instructions.
- Recommended valve installation depth 1-5/8" to 2-3/8".
- Included Rough-in valves:
- Thermostatic rough-in valve features scald guard protection, high temperature limit stop, integral water stops and check valve, a ceramic cartridge, and a bronze valve body.
- Volume control rough-in valve features a ceramic disc cartridge and brass valve body.
- Diverter valve features a ceramic disc cartridge and brass valve body. An available Single-Function Diverter valve Cartridge restricts water flow to one outlet at a time.

VOLUME CONTROL ROUGH-IN VALVE

SKU: 948546 SH6020, SH6040






HIBISCUS IN-WALL SHOWER VOLUME CONTROL HANDLE


SKU: 948557

SHHB9007, SHHB9007Z



OPTIONAL VOLUME CONTROL ROUGH-IN VALVE WITH 1/2" -OR- 3/4" CONNECTION


SKU: 948557 SH6020, SH6040



HIBISCUS THERMOSTATIC SHOWER VALVE


SKU: 948558


SHHB9009, SHHB9009Z



HIBISCUS OPTIONAL THERMOSTATIC VALVE WITH 1/2" -OR- 3/4" CONNECTION

SKU: 948558 SH6004, SH6006






HIBISCUS IN-WALL SHOWER DIVERTER

SKU: 948902

SHHB9005, SHHB9005Z






HIBISCUS OPTIONAL 3-WAY IN-WALL DIVERTER ROUGH-IN VALVE - 3/4"


SKU: 948902


SH6103





SWIVEL WATER SUPPLY ELBOW AND BRACKET FOR HAND SHOWER

SKU: 948936 SHWES2050











60" STRETCHABLE METAL HAND SHOWER HOSE

SKU: 948938 SHH1010






MODERN SQUARE WALL-MOUNT SHOWER ARM WITH FLANGE

SKU: 948956

SHRSA120S, SHRSA120SZ, SHRSA180S, SHRSA180Z



3-WAY IN-WALL DIVERTER ROUGH-IN VALVE

SKU: 953056 SH6101, SH6103

