

HANGING TEAK SHELF

SKU: 949633

BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures. Signature Hardware accepts no liability for any damage to the wall, shelf, or for personal injury during installation.

Observe all local plumbing and building codes.

Unpack and inspect the product for shipping damage. If any damage is found, contact our Customer Relations team at 1-866-855-2284.

GETTING STARTED

• Ensure that you have gathered all the required materials that are needed for the installation.

TOOLS AND MATERIALS:







Stud Finder

Pencil

Tape Measure





Level

Drill

For Warranty information, please visit: signaturehardware.com/services/warranty

REVISED 01/30/2020 CODES: 521487, 521488



HANGING TEAK SHELF

SKU: 949633

INSTALLATION

1. Locate and mark the position of the wall studs to which you will fasten your teak shelf. You can find studs by listening for a solid sound as you knock on the wall or by using a stud finder.

Important: If the studs in your bathroom do not line up to the mounting location for your shelf, wood blocking can be installed between the studs using standard 2 x 4's. If the wood blocking needs to be installed behind the finished wall, we recommend consulting a professional if you are unfamiliar with this type of installation.

- 2. Determine and mark the mounting location. Use a level to ensure the shelf is perfectly straight.
- 3. Measure the location of the keyhole brackets on the back of the shelf to determine the location of your mounting hardware.
- 4. Drill pilot holes and install the mounting hardware. Because wall construction and materials vary from home to home, the appropriate mounting hardware may need to be purchased from your local hardware store. Consult a professional if you are unfamiliar with this type of installation.
- 5. With the help of another person, hang your teak shelf by attaching the keyhole brackets to the mounting hardware.

