

THREE-BALL GOOSENECK

TUB WALL-MOUNT FAUCET

SKU: 900491

BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing plumbing fixtures. Signature Hardware accepts no liability for any damage to the faucet, plumbing, sink, counter top, or for personal injury during installation.

Observe all local plumbing and building codes. Unpack and inspect the product for shipping damage. If any damage is found, contact our Customer Relations team via live chat at www.signaturehardware.com or by emailing support@signaturehardware.com.

GETTING STARTED

Ensure that you have gathered all the required materials that are needed for the installation.

For these instructions, it is assumed that the old faucet has been completely removed and any necessary repairs or modifications to the water supply have been completed.

ADDITIONAL QUESTIONS?

Still need help? Check out our Help Center at www.signaturehardware.com for product and warranty information, or contact us through live chat or by emailing support@signaturehardware.com.

TOOLS AND MATERIALS:



Adjustable
Wrench



Basin
Wrench

REVISED 02/17/2021
CODES: 515186, 508305, 508306

THREE-BALL GOOSENECK

TUB WALL-MOUNT FAUCET

SKU: 900491

INSTALLATION

1. Remove lock nuts from the back or bottom of the faucet and insert faucet through mounting holes.
2. Hand-tighten washers (if included) and hex nuts to secure.
3. Check to make sure the faucet is properly aligned and adjust as needed. When the faucet is in the proper position, finish tightening the hex nuts with your adjustable wrench
4. Attach the hot and cold water feed tubes to the water inlets on the back, or bottom of the faucet. (Hot water is always on the left and cold water is always on the right)
5. Finish your installation by attaching any hoses and/or handles that might be included.
6. After all connections have been made, turn on the water supply, check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the faucet on and allow the water to flow through the spout for approximately 60 seconds. If you have a hand shower, divert the water to the hose and allow the water to flow through the hose for an additional 60 seconds.