



BATHROOM SINK DRAIN

INSTALLATION INSTRUCTIONS

Before installing, read entire Bathroom Sink Drain Installation Instructions. Observe all local building and safety codes.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1.855.715.1800. If you need assistance or have questions while installing your drain, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures. Signature Hardware accepts no liability for any damage to the sink or drain, or for personal injury during installation.

TOOLS AND MATERIALS: Thread Sealant Basin Wrench

INSTALLATION

1. Disassemble the drain by removing the threaded tail piece (**F**), rubber sealing gaskets (**B**, **C**), friction washer (**D**), and lock nut (**E**).
2. Place thread sealant on the threaded section of the tail piece (**F**). Thread the tail piece (**F**) onto the threaded shank (**A**).
3. Slide the flat rubber sealing gasket (**C**) up the tail piece to the top of the threaded shank. This gasket will create a seal between the drain flange and the sink.
4. Place the drain in the drain hole in the sink.
5. On the underside of the counter, attach the tapered rubber gasket (**B**). With the flat side facing down, slide the gasket up the threaded shank until it makes contact with the bottom of the sink or counter.
6. Slide the friction washer (**D**) up to meet the rubber gasket. Thread the lock nut (**E**) onto the threaded shank. Hand-tighten and make sure that the drain is properly aligned. When ready, finish tightening with a basin wrench to secure the drain.

