



COPPER DROP-IN SINK

INSTALLATION INSTRUCTIONS

Before installing, read entire Drop-In Sink Installation Instructions. Observe all local building and safety codes.

For this installation it is assumed that the countertop has been cut to the dimensions of the sink. We recommend consulting a professional if you are unfamiliar with this type of installation, Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your sink, contact Customer Service.

TOOLS AND MATERIALS:

Neutral Cure Silicone Sealant
Thread Sealant

Damp Cloth
Basin Wrench

Level

INSTALLATION

1. Lower the sink into the sink cutout on the counter to confirm the sink will fit properly. The perimeter of the sink rim should connect with the counter while the sink bowl should sit completely inside the counter.

Tip: For easier installation, install the drain and faucet before attaching the sink to the counter.

2. Remove the sink and run a bead of neutral cure silicone sealant around the sink cutout to seal the rim against moisture and leaks.
3. Carefully lower the sink back into the cutout and press the sink firmly into the sealant. Make sure that the sink is level and properly aligned.
4. With the sink in place, tighten the mounting clips (if included) on the underside of the sink.
5. Wipe away any excess sealant around the rim of the sink with a damp cloth.

DRAIN INSTALLATION

1. Apply a bead of silicone sealant to the base of the strainer flange.
2. Place the flange in the drain opening in the kitchen sink.
3. If your drain has a disposer flange, use the directions supplied with the garbage disposer to attach the disposer and complete your installation. For drains with strainer baskets, slide the rubber gasket and friction washer up the strainer flange to the bottom of the sink.
4. Thread the lock nut onto the drain assembly. Hand-tighten and make sure that the drain is properly aligned. When ready, finish tightening with a basin wrench to secure the drain.
5. Secure the P-trap to the strainer flange with the provided compression nut and ferrule.



MATERIAL DESCRIPTION AND CARE

Copper sinks are specially designed for both durability and beauty. Created with a single sheet of heavy gauge copper, our copper sinks have no internal welds, strengthening the structure and preventing leakage.

Copper sinks will patina with time and normal use, creating a much sought-after living finish. Because of copper's natural composition, cleaning is easy. Simply rinse after each use to rid the surface of any soap or dirt and wipe dry. Apply wax, such as Table Top Wax, at least once every 15-20 days to keep your copper sink in its original condition and prevent the natural aging process. For a more thorough cleaning, wash occasionally with dish soap and a sponge.

Do not use copper or silver cleaners, or any abrasive or harsh chemicals on your copper sink. Avoid contact with hot pots or pans, as this may cause distortion due to copper's low melting temperature.