



GRAB BAR

BEFORE INSTALLING

Read entire grab bar installation instructions. Observe all local building and safety codes.

INSTRUCTIONS

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your grab bar, contact Customer Service.

In order to support the maximum weight limit, grab bars must be anchored to solid wood blocking installed between wall studs. We recommend consulting a professional if you are unfamiliar with this type of installation.

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures. Signature Hardware accepts no liability for any damage to the floor, walls or for personal injury during installation.

TOOLS AND MATERIALS:



Stud Finder



Pencil



Level



Drill



Masking Tape




Screwdriver

INSTALLATION

1. Slide or unthread the decorative escutcheon to expose the wall flange.
2. Determine the installation location and mark the location of the mounting holes using the template (if included) or wall flange. This location will vary, we recommend installing your grab bar approximately waist high for the user. Use a level to verify that your grab bar is properly aligned.

Wall Flange Front View



3. Drill mounting holes using the appropriate drill bit for the wall surface or material.

Tip: Place masking tape in the installation location when marking the mounting holes to see the outline clearly and keep your drill from damaging the mounting surface.

4. Remove masking tape from the installation location if applicable.
5. Attach the grab bar to the wall with the mounting screws provided.
6. Slide or thread the decorative escutcheons over the wall flanges and press firmly in place to complete installation.

