



# UNDERMOUNT SINK

## BEFORE INSTALLING

Read entire Undermount Sink Installation Instructions. Observe all local building and safety codes.

## INSTRUCTIONS

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your sink, contact Customer Service.

For this installation it is assumed that the countertop has been cut to the dimensions of the sink. We recommend consulting a professional if you are unfamiliar with this type of installation, Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Use care when lifting and installing any sink. Place sink on a level surface with a towel or other soft cloth beneath to prevent damage.

## TOOLS AND MATERIALS:



Thread Sealant



Silicone Sealant



Pencil



Damp Cloth

## INSTALLATION

1. Carefully turn the countertop over so that it rests upside-down on a stable, cushioned surface.
2. Position the undermount sink over the sink cutout on the counter. Make sure the sink is centered with the faucet hole and is evenly spaced between the bolt holes.
3. Draw an outline of the sink on the countertop, once the ideal position is determined.
4. Remove the sink from the countertop. Apply a generous bead of silicone around the sink rim.
5. Carefully place the sink upside down on the countertop, positioning it within the outline.
6. Attach the sink clips (if included) by placing the long end of the bracket flat against the sink lip. Screw the wing bolts through the brackets and bolt holes and tighten snugly.
7. Carefully turn the counter and sink over.
8. Remove any excess silicone with a cloth moistened with water or mineral spirits. Let silicone dry according to manufacturer's instructions.