



TUB DRAIN

INSTALLATION INSTRUCTIONS

Before installing, read entire Bathroom Sink Drain Installation Instructions. Observe all local building and safety codes.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1.855.715.1800. If you need assistance or have questions while installing your drain, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures. Signature Hardware accepts no liability for any damage to the sink or drain, or for personal injury during installation.

TOOLS AND MATERIALS:

PVC Cement

Hacksaw

Silicone Sealant

INSTALLATION

1. Trim the 1- $\frac{1}{2}$ " PVC drain pipe extending from the floor to the appropriate length. This can be determined by attaching the drain to the tub and measuring the distance from the finished floor to the center of the fitting socket.
2. Remove the drain from the tub, and attach the hub adapter to the PVC pipe with PVC cement. Place the rubber washer on the rim of the hub adapter.
3. Lift and place the tub in position over the drain.
4. Place the pop up, or lift and turn drain in the hub adapter and verify that everything is aligned properly. Make any necessary changes.
5. Run a bead of silicone sealant along the underside of the drain and thread the drain into the hub adapter. Remove any excess sealant with a damp cloth. Allow silicone to dry for 24 hours before use.