



## WIDESPREAD FAUCET

### INSTALLATION INSTRUCTIONS

Before installing, read entire Widespread Faucet Installation Instructions. Observe all local building and safety codes. For the following installation instructions for your new Widespread Faucet it is assumed that any old fixtures have been removed and any repairs or modifications to the water supply have been completed.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-855-715-1800. If you need assistance or have questions while installing your faucet, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing kitchen fixtures. Signature Hardware accepts no liability for any damage to the floor, walls, plumbing or for personal injury during installation.

Turn off the water supply at the sink where the new faucet is being installed.

### TOOLS AND MATERIALS:

Adjustable Wrench

Basin Wrench

Allen Wrench (provided)

### INSTALLATION

1. If your faucet comes with a brass T attached to the faucet body, remove the T and associated hardware.
2. Place the mounting washer and rubber sealing gasket on the faucet body.
3. Thread your faucet body through the center mounting hole.
4. From underneath the sink, screw the mounting hardware and brass T onto the faucet body and hand-tighten to secure.
5. Check to make sure the faucet is properly aligned and adjust as needed. When the faucet is in the proper position, finish tightening mounting hardware with your adjustable wrench.
6. Disassemble the handle body. You may need to remove set screws located in the side of the handle with a hex, or Allen, wrench (provided).
7. Insert the handle body up through the mounting hole. Secure the handle assembly to the handle body. Make sure that the rubber sealing gasket is between the handle and the mounting surface to ensure a water tight seal.
8. With the handle in the OFF position, tighten the set screw on the top or side of the handle with your Allen wrench.
9. Repeat steps 6-8 to install the remaining handle (if included).
10. If your faucet features a side spray, install by inserting the sprayer housing and rubber sealing gasket through the appropriate mounting hole. Secure by tightening the lock nut from underneath the sink. If your faucet does not have a side spray, move on to step 12.



11. Attach the spray nozzle to the spray hose (if not already attached), and insert the side spray hose through the sprayer housing. Attach the hose to the spray hose outlet on the faucet.

**Tip:** Before you connect the spray hose to the faucet, make sure that it is in a position that will allow you to pull it out easily without getting caught on any other fixtures beneath the sink.

12. If a soap dispenser is included, install by threading the pump handle through the appropriate mounting hole and attaching the plastic soap reservoir from underneath the sink.

13. Hand tighten to attach the hot and cold flexible water feed tubes to the handle bodies and brass T. Give a  $\frac{1}{4}$  turn with pliers or wrench, but don't over tighten. (Hot water is always on the left and cold water is always on the right.) Curve tubes as necessary to ensure there are no kinks or knots.

14. Connect the main water supply to the faucet body.

15. After all connections have been made, turn on the water supply, check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the faucet on and allow the water to flow through the spout for approximately 60 seconds. Divert the water to the spray hose and allow the water to flow through the hose for approximately 60 seconds.